

INSULADD

Insulation Additive For Paint

Don't Just Paint, Insulate!

High Insulating Value ●
Save \$ On Heating And Cooling ●
Easy To Use ●
Easy To Order ●

Approved vendors for Sherwin-Williams Paints (Vendor # 0025458524)

Materials Safety Data Sheet

Identification of product:

Product name - INSULADD
Manufacturer - Tech Traders, Inc
Address - 307 Holly Road, Vero Beach, Fl 32963
Telephone Number - 561-231-5233
Sales Name - INSULADD
TSCA CAS Registry Numbers - This product is a mixture under TSCA.
CAS Numbers for identification purposes are: 1302-93-8, 1335-30-4
DOT Hazard Class - Not Applicable
DOT Shipping Name - Not Applicable

Chemical and physical data:

Appearance & Odor - Dry white powder, odorless
Specific Gravity (liquids only) - Not Applicable
Bulk Density - 0.4 g/cc
Solubility in Water - Negligible
pH. - Not Applicable
Ingredients- Ceramic Microspheres

Fire, Explosion and Reactivity Hazard Data:

Flash Point (° F) - Noncombustible
Special Fire Fighting Procedures - Not Applicable
Stability - Stable
Conditions to Avoid - None known
Incompatibility (materials to avoid) - None Known
Hazardous Decomposition Products -None

Spills and Disposal:

Environmental Hazard - None Known. Not listed as a toxic chemical
under SARA Title III, §302, §304, or §313
Spillage - Sweep, scoop, or vacuum material
Waste Disposal Method - Landfill according to local, state and federal
regulations. Disposed material is not a RCRA hazardous waste.

Health Hazard Data:

Eye Contact -	Causes irritation
Skin Contact -	May cause dehydration and irritation
Inhalation -	Causes irritation to respiratory tract
Chronic Hazards -	No known chronic hazards. Not listed by OSHA, NTP or IARC as a carcinogen
Signs and symptoms of exposure -	Sneezing and dryness of mucous membranes (inhalation). Redness and tearing (eye exposure). Dryness, itching or burning (skin exposure).
Medical conditions aggravated by exposure -	Asthma and lung diseases
First aid procedures -	In case of contact immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists. If inhaled, remove to fresh air

Special Protection Information:

Respiratory protection -	Use NIOSH-certified dust respirator where dust occurs. Observe OSHA regulations for respirator use (29 CFR 1910.134)
Gloves -	Cotton gloves are usually sufficient to protect hands from irritation arising from handling this product
Eye protection -	Chemical goggles
Other protective equipment -	Safety shower and eyewash fountain should be within direct access
Personal hygiene -	Avoid breathing dust. Wash thoroughly after handling
Engineering control -	Use with adequate ventilation

Substances For Which Standards Have Been Set:

OSHA permissible exposure limit or ACGIH threshold limit value have not been established. PQ recommended ceiling limit 5mg/m³

Exposure analysis methods - Respirable sampler or midjet impinger see. J. Am. Ind. Hyg. Assoc., 28.554 (1967)

TECH TRADERS INC.

307 Holly Rd., Vero Beach, FL 32963

Toll Free: 888-748-5233 Fax: 561-231-5959 www.insuladd.com email: info@insuladd.com